



SKYEDGE II-C GEMINI-E S2X

Enterprise High-Speed VSAT



ENABLING HIGH-SPEED BROADBAND SERVICES

SkyEdge II-c Gemini-e is a high-throughput VSAT designed to enable high-speed enterprise broadband Internet services. The Gemini-e VSAT enables fast web browsing, video streaming, IPTV, VoIP, and other bandwidth-intensive services. This solution is ideal for markets such as retail, banking, ATMs, SCADA, M2M and lotteries, as well as USO/USF and government-funded programs aimed to expand broadband connectivity to underserved regions.

Gemini-e includes a full-featured IP router, eliminating the need for an external router through its support of enhanced IP routing features such as DHCP, NAT/PAT, VLANs, routing protocols, IPSEC client and IGMP.

Advanced QoS guarantees the performance of real-time applications such as VoIP and video streaming while simultaneously enabling additional data applications. Gemini-e also supports next-generation IPv6 networking. To ensure fast web browsing and a high-quality user experience, Gemini-e contains a full set of protocol optimization and application acceleration features, and the highest level of transmission security to protect all user traffic.

ADVANCED VSAT PLATFORM FOR ENTERPRISE

Based on the latest-generation ARM technology, Gemini-e enables high-speed services while employing full link encryption, TCP and HTTP acceleration.

The terminal includes an intuitive, web-based Graphical User Interface to assist the user during the installation and service activation process.

ENHANCED CENTRAL SERVICE MANAGEMENT INTERFACE FOR VNOS

Gemini-e is part of a complete VSAT ground system that includes an advanced Network Management System (NMS) and facilitates service management available to VNOs via an electronic B2B interface.

SkyEdge II-c Service Management enables VNOs to manage their services totally independent of the satellite network operator, providing a complete management suite. This includes real-time viewing of the service status, events, alarms and statistics.

BENEFITS

- Includes advanced QoS, VLANs and routing protocols supporting enterprise services
- Fast web browsing with web acceleration and compression
- Enables high-quality VoIP and video
- Simple installation and service activation
- Forward and return adaptive transmission technologies
- Central monitoring and service management
- Supports C, Ku and Ka bands



SUPERIOR VSAT TECHNOLOGY

Designed to support the latest standard and high throughput satellites, Gemini-e's advanced adaptive transmission technologies maximize performance and improve service availability. Gemini-e is based on Gilat's VSAT technologies, which power over a million terminals worldwide.

MAXIMUM SPECTRAL EFFICIENCY

Gilat's innovative transmission technologies deliver exceptional performance and space segment efficiencies. Wideband DVB-S2X carriers in the forward direction and adaptive transmission in the return direction enables maximum service availability and highest bandwidth efficiency at any transmission condition. This is achieved by adaptive power control, changes to the carrier symbol rate, ModCod and spread-spectrum factor per VSAT on a per time-slot basis.

TECHNICAL SPECIFICATIONS

FORWARD CHANNEL

Standard:

DVB-S2X Adaptive Coding and Modulation (ACM)

Carrier Rate: 1.5Msps-500Msps**Roll-off:** 0.05, 0.1**Modulation:**

QPSK, 8PSK, 16APSK, 32APSK, 64APSK, 256APSK

Coding: LDPC, BCH**FEC:**

DVB-S2X FECs

RETURN CHANNEL

Access Scheme:

MF-TDMA, Dynamic Channels

Inbound Rates:

Symbol rate - 128Ksps-12Msps

Modulation: BPSK, QPSK, 16QAM**Coding:** LDPC**FEC:**

1/4, 1/3, 2/5, 1/2, 2/3, 3/4, 5/6, 8/9

MODEM INTERFACES

RF Input / Output:

Two female F connectors, 75 Ω

RF in frequency - 950-2150MHz

RF out frequency - 950-2400MHz

DISEqC

Data Interfaces:

1 x Ethernet 10/100/1000BaseT

RJ-45, 802.1q VLAN

Management Interface:

Web-based local management,

Remote software upgrades over

the air, SNMP

ENHANCED FEATURES

IP Features:

IPv4/IPv6, TCP, UDP, ICMP, DHCP,

NAT/PAT, DNS Caching, cRTP,

IGMPv2, SIP, DiffServ, VLANs,

RIPv2, Static Routes

QoS:

Per VSAT and per Managed Group, CIR, MIR, CBR, DiffServ and priority-based queuing, applicationbased priority

Security:

- AES-256 bit link encryption

- IPSEC Client

- ACL Firewall

- X.509 Terminal Authentication

Application Acceleration and**Protocol Optimization:**

- TCP acceleration

- HTTP web pre-fetch acceleration and compression

ENVIRONMENTAL AND MECHANICAL

Dimensions:

153 x 140 x 35mm (WxDxH)

Operating Voltage:

- 100V-240V AC Auto Range

- 11V-60V DC

Operating Temperature:

0°C to +50°C

Certifications: CE, FCC, EMC

OUTDOOR UNIT (ODU)

Frequency Bands: C, Ku, Ka**Transmit Power:** Via IDU 24V**Antenna Size:** 0.7m and higher**Operating Temperature:**

-40°C to +60°C